

## Make Restoring Your Exterior Wood EASY!



### Are you ready to bring your exterior wood back to life?

Weather and time can make wood look dingy and gray well before its replacement time. **Restore-A-Deck** removes that grunge and film to bring your wood back to looking like **NEW!**

Restore-A-Deck Cleaner and Brightener is a **two-part system** for a powerful and eco-friendly restoration process. First **Restore-A-Deck Cleaner** deep cleans your wood, then **Restore-A-Deck Brightener** lowers the pH and significantly brightens the wood.

Once you have prepared your exterior wood project with the **Restore-A-Deck** system the stain or finish you choose will look and last its very best!

- Concentrated, one container makes 5 gallons
- Prepares wood for any type of finish or re-coating
- Restores weathered wood to its natural color
- Eco-Friendly



for purchase or product information

1-866-856-3325 or visit

[www.twpstain.com](http://www.twpstain.com)




## TWP is easy to apply!




### SURFACE PREPARATION

**New Wood:** It is necessary to allow new wood to age four to twelve months before staining.



**Old Wood:** Untreated old wood can be revived to look like new using a mild bleach and water solution or **Restore-A-Deck** followed by a 1500-2500 p.s.i. output power washer. Previously stained wood may require a chemical stripping or brightening agent such as "Injectable Safe Strip" combined with power washing to remove all of the old coating.



When working with a power washer use caution to avoid excess fraying of the wood surface. Allow 36 to 48 hours of dry time before TWP® application.

### TWP PRESERVATIVE APPLICATION

- Mix preservative thoroughly
- Apply TWP® by brush, pump sprayer or roller
- Saturate surface with TWP®
- Do not let TWP® puddle
- Excessive product that does not penetrate and is not removed may cause premature failure
- If needed, apply second coat wet on wet
- Overnight dry time (depending on temperature and humidity)
- Do not thin TWP®
- Clean-up with mineral spirits
- Do not apply below 50° F or above 90° F
- Coverage Rate: 200-400 sq. ft. per gallon

TWP® 1500 series is designed to penetrate the wood surface and not build a film. Apply as much material as the wood can absorb. Over application may leave an oily residue on the surface and may cause premature failure of the stain. Any material that has not penetrated 1 hour after application must be removed.



### WATER REPELLENT

Resists warping, cracking and splitting. Prevents freeze damage in colder climates.

### PREVENTS PREMATURE UV DAMAGE

UV absorbing pigments prevent premature graying, darkening and fading.

### PREVENTS WOOD ROT

Wood preservative prevents structural damage and decay for above ground surfaces. Specially formulated for log homes, decking, fences, roofing and siding.

### MILDEW RESISTANT

Inhibits growth of mold and mildew on the surface, preventing premature discoloration. Decks, log homes, fences and wood siding stay new looking longer.

### EASY TO APPLY

Penetrating, long lasting formula is easy to apply and easy to maintain.

**Note:** TWP® 1500 clear contains no UV absorbing pigments and will allow the wood to gray.

Your Local TWP Dealer

[www.twpstain.com](http://www.twpstain.com)

866-856-3325

Official TWP Online Dealer



AN EMPLOYEE OWNED COMPANY

01/2018



## 1500 Series Semi-Transparent Exterior Wood Stain



**LOW VOC FORMULA**  
350 g/l max



# Preserve & Protect Your GREAT OUTDOORS!